

Power Foam Tape

IMPORTANT NOTE

Double-sided foam tape for permanent and long term application to practically all smooth and slightly uneven surfaces!

com2C GmbH & Co. KG
Industrieweg 1
DE – 32457 Porta Westfalica

info@com2-c.de
www.com2-c.de
Tel: + 49 (0) 57 33 87 85 88
Fax: + 49 (0) 57 33 87 85 88 9

Technical data

Liner:	yellow Polyethylenfilm
Adhesive:	Acrylat Power Foam
Film:	Polyethylen
Thickness:	approx. 1.10 mm
Tack mN/mm ² :	40N/625mm ² /26N/25mm

General information

- Double-sided foam tape
- Permanent application on smooth and slightly uneven surfaces

Areas of use/application

- kitchen splashback panels, AluDibond, Mirrors, metal panels
- Can be used on lacquer, glass / ceramic, wood
- high-energy plastics: PVC, PC, ABS
- low-energy plastics: PE, PP Metal, paper / cardboard

Advantages

- Vibration-dampening and compensating for different expansion coefficients of the joining partners.
- Extremely aging, UV, weather and plasticizer resistant
- The Power Foam does not yellow and remains permanently elastic
- Application security through high initial adhesive strength
- The final bond strength is achieved after a dwell time of 24 hours

These technical information is given based upon normal technical standards and our findings and experience. Due to the multitude of parameters and conditions this product may be used under, every organisation and individual using this product is obliged to test this product for suitability and usability regarding the desired application in own responsibility. Changes reserved. With every newer version, this version loses validity.

Power Foam Tape

IMPORTANT NOTE

Double-sided foam tape for permanent and long term application to practically all smooth and slightly uneven surfaces!

Processing instructions

- The surface should ideally be smooth or slightly uneven, dust-free, clean, free of solvents, silicones and oils.
- The optimal room climate during processing is included
- 18 °C - 35 °C and a humidity of 50% - 70%.

Additional information

- Further information about this and other products can be found on our website: www.caleidoscop.com
- Please store rolls always together with the label / the batch number. Without these, no complaints can be processed.
- Shelf life: 12 months
- All measurements were made under standard climate conditions.

com2C GmbH & Co. KG
Industrieweg 1
DE – 32457 Porta Westfalica

info@com2-c.de
www.com2-c.de
Tel: + 49 (0) 57 33 87 85 88
Fax: + 49 (0) 57 33 87 85 88 9

These technical information is given based upon normal technical standards and our findings and experience. Due to the multitude of parameters and conditions this product may be used under, every organisation and individual using this product is obliged to test this product for suitability and usability regarding the desired application in own responsibility. Changes reserved. With every newer version, this version loses validity.