

## Silverback 250 PES WBL M W FR

PES Polyester • WB Waterbased inks • L Latex inks • M Matte • W White •  
FR Flame Retardant



com2C GmbH & Co. KG  
Industrieweg 1  
DE – 32457 Porta Westfalica

info@com2-c.de  
www.com2-c.de  
Tel: + 49 (0) 57 33 87 85 88  
Fax: + 49 (0) 57 33 87 85 88 9

### Technical Data

Weight:	approx. 250g/m <sup>2</sup>
Thickness:	approx. 270µm
Composition:	IJ-printable Polyester fabric + PU blackout coating
Surface:	white fabric
Reverse side:	silver, smooth
Flame Retardant:	B1 test certificate according DIN 4102-1

### General Information

- 100% Polyester fabric with blackout backside coating
- B1 test certificate according DIN 4102-1
- Printable with waterbased dye, pigment and latex inks
- High-quality ink receptive coating
- Extremely wrinkle-resistant
- Soft touch
- Good water and scratch resistance

### Areas of application

- Indoor advertising
- RollUp Display systems
- Hanging banners
- Backdrops
- Sunblinds, Window blinds
- Banners, Displays, Frames, Exhibitions, etc.

These technical information is given based upon normal technical standards and our findings and experience. Due to the multitude of parameters and conditions this product may be used under, every organisation and individual using this product is obliged to test this product for suitability and usability regarding the desired application in own responsibility. Changes reserved. With every newer version, this version loses validity.

## Silverback 250 PES WBL M W FR

**PES** Polyester • **WB** Waterbased inks • **L** Latex inks • **M** Matte • **W** White •  
**FR** Flame Retardant

com2C GmbH & Co. KG

Industrieweg 1

DE – 32457 Porta Westfalica

info@com2-c.de

www.com2-c.de

Tel: + 49 (0) 57 33 87 85 88

Fax: + 49 (0) 57 33 87 85 88 9

### Advantages

- High quality, water-resistant coating
- Very good resistance to cracking
- Extremely good lay-flat properties, no curl
- Soft textile touch
- Scratch resistant
- Blockout construction
- PVC-free

### Printability

- Very good print results using waterbased dye, pigment and latex inks
- Intense, brilliant colors
- Quick drying, no bleeding
- Good water and scratch resistance

### Processing instructions

- Prior to conversion / further processing, the prints must be allowed to thoroughly dry. We recommend a drying time of 24 hours.
- Material and prints are not washable.
- Optimum processing conditions 18° - 25°C and a humidity of approx. 40% - 65%.

### Additional information

- Further information about this and other products can be found on our website:  
[www.caleidoscop.com](http://www.caleidoscop.com)
- The printside / winding, length and widths of the material rolls can be tailored to your needs, respecting our minimum manufacturing quantities. Please ask us for special sizes / special conversion options!
- Please store rolls always together with the label / the batch number. Without these, no complaints can be processed.
- Shelf life: 12 months
- All measurements were made under standard climate conditions.

These technical information is given based upon normal technical standards and our findings and experience. Due to the multitude of parameters and conditions this product may be used under, every organisation and individual using this product is obliged to test this product for suitability and usability regarding the desired application in own responsibility. Changes reserved. With every newer version, this version loses validity.