

## FloorGraphic Tex 350 LUVES M W adh

## Technical Datasheet


L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · adh self-adhesive

Version: 03-2022

### Inks



### Application and Properties



### Technical Data

<b>Film thickness:</b>	350 µm (± 10)
<b>Basic weight:</b>	approx. 422 g/m <sup>2</sup> (± 10) (incl. adhesive and liner)
<b>Composition:</b>	matt, structured polyester textile + strong-adhesive - reversible + PE liner, siliconized on both sides
<b>Liner:</b>	105 g/m <sup>2</sup> PE paper siliconized on both sides
<b>Surface:</b>	Matte white
<b>Shelf life:</b>	1 year properly stored at 15° - 20°C

### General Information

- 100% polyester textile with anti-slip coating
- R11 certified
- PVC free
- Temporate floor graphic advertising/eye catch on smooth floor-tiles, carpets and for wall covering without protective film for both indoor and outdoor application
- Very good anti-slip properties when wet and dry
- No shrinkage
- Simple and bubble-free adhesion
- Removable with reversible adhesive

### Application

- Advertising and universal signage
- Floor graphics and eye catchers
- Wall covering

### Advantages

- Dry, bubble-free, clean, quick and easy application
- Reversible adhesive with very good adhesion
- Removable
- No shrinkage
- None reflective
- Vertical adhesive application
- PVC-free

## FloorGraphic Tex 350 LUVES M W adh

## Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · adh self-adhesive

Version: 03-2022

### Printing Properties

- Printable with latex, UV curing, eco solvent and solvent inks
- No bleedings even with high ink limit
- High color brilliance
- Fast drying

### Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The substrate must be dry, clean and smooth
- Roller or felt squeegee recommended to be without sharp edges
- To avoid fingerprints, the use of cotton gloves is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

### More information

- You can find more information on our products on [www.com2-c.de](http://www.com2-c.de)
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 15° - 20°C

### Available sizes

- 30 m x 137,0 cm (54'')

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-command that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.