



Inks**Application and Properties****Technical Data**

Composition:	monomeric plasticized PVC
Thickness:	approx. 100 µm
Liner:	Single side siliconized white paper
Basic weight:	135 g/m ² siliconized paper
Adhesive:	Transparent, water-based dispersion dot formed adhesive
Adhesive weight:	approx. 15g/m ²
Surface:	Glossy white

General Information

- Monomeric plasticized PVC
- Dot form transparent adhesive
- Printable with latex, UV-curable, eco solvent and solvent inks
- Glossy and even surface
- Fast drying
- High color brilliance
- For short- and medium-term indoor application

Application

- For short so as medium-term indoor advertising application
- Easy application on both even and uneven surfaces
- Suitable for Events, trade fair and shop fittings
- Signs, marking

Advantages

- Easy drying, no bleeding even with high inks limit
- Good and reliable adhesion
- Easy and simple applications without bubbles or wrinkles
- Easy to remove without leaving any residue

Printing properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High color brilliance
- Fast drying
- Water and scratch resistant

Processing instructions

- Prints must be completely dry before further processing; a drying time of 24 hours is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%.

More information

- You can find more information on our product portfolio on www.com2-c.de
- We can manufacture your product and customize the surface, lengths and widths individually to meet your requirements. We will need a MOQ.
- Always store rolls together with the label and batch number. Without the reference batch number, no complaints can be processed.
- Our tests are carried out in a standard climate condition.

Available sizes

- 50m x 106,7cm (42") | 50m x 137,0cm (54")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.