

Inks**Application and Properties****Technical Data**

Film thickness:	80µm polymeric PVC film
Total thickness:	approx. 230 µm (incl. adhesive and liner)
Composition:	Polymeric PVC + permanent adhesive + embossed PE paper backing
Liner:	135 g/m ² double-sided siliconized PE paper, embossed
Surface:	Matt, frosted (sandy effect)
Adhesive:	Polyacrylate
Adhesion:	Immediately: 8.8 N/25 mm after 20 min: 13.3 N/25 mm after 24 hours: 19.8 N/25 mm
Shelf life:	7 years indoors when laid vertically 4 years outdoors with vertical bonding
Storage:	2 years when properly stored at 15° to 20°C

General Information

- Polymeric PVC glass decoration film with a sandy effect
- Embossed liner for dry and easy application
- Very good UV light stability and water resistance
- Very good scratch resistance

Application

- All smooth and transparent surfaces such as windows, glass doors, shop windows, mirrors etc.
- Very easy to plot and suitable for contour cutting

Advantages

- Dry, bubble-free, clean and quick application thanks to the embossed liner
- Can be corrected easily and without creasing
- Permanent adhesive with good and reliable adhesion

Processing instructions

- Prints must be completely dry before further processing; a drying time of 24 hours is recommended
- Keep the surface dry, clean, absorbent and smooth
- Roller or felt squeegee recommended to be without sharp edges
- To avoid fingerprints, the use of cotton gloves is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions

Available sizes

- 25m x 105,0cm (41.3") | 25m x 127,0cm (50") | 25m x 137,0cm (54") | 25m x 160,0cm (63")

<p>This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.</p>	
---	--