


Inks**Application and Properties****Technical Data**

Film thickness :	200 µm (± 10), monomeric matt embossed PVC
Total thickness:	approx. 360 µm (incl. adhesive and liner)
Composition:	Embossed PVC + reversible adhesive + embossed PE paper liner
Liner:	140 g/m ² one-side siliconized, embossed PE paper
Surface:	Matte white
Adhesive:	Polyacrylate
Adhesive strength:	Initial: 4.7 N/25 mm after 20 min: 4.3 N/25 mm after 24 hours: 9.0 N/25 mm
Storage	1 year when storing properly at 15° - 20°C

General Information

- Short-term floor graphic advertising without protective lamination for indoor application
- Easy and bubble-free application through air holes in the adhesive created by embossed liner
- Removable with reversible adhesive
- Can be used on smooth floor for coverings, e.g. on ceramic tiles
- Also suitable for vertical application
- Printable with latex, UV-curable, eco solvent and solvent inks
- Very good scratch resistance
- R9 certified

Application

- Fairs and shop fitting
- Floor graphics and eye catchers

Advantages

- Dry, bubble-free, clean, quick and easy application
- Reversible adhesive with very good adhesion
- Removable

Printing Properties

- Printable with latex, UV curing, eco solvent and solvent inks
- No bleedings even with high ink limit
- High color brilliance
- Fast drying

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The substrate must be dry, clean and smooth
- Roller or felt squeegee recommended to be without sharp edges
- To avoid fingerprints, the use of cotton gloves is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 15° - 20°C

Available sizes

- 30 m x 137,0 cm (54'')

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.