


## FloorGraphic 160 LUVESS M W air rem adh

## Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · air embossed cover  
rem removable · adh self-adhesive

Version: 03-2022

### Inks



### Application and Properties



### Technical Data

<b>Film thickness :</b>	160 µm (± 10), monomeric matt embossed PVC
<b>Total thickness:</b>	approx. 360 µm (incl. adhesive and cover)
<b>Composition:</b>	Embossed PVC + reversible adhesive + embossed PE paper liner
<b>Liner:</b>	140 g/m <sup>2</sup> one-side siliconized, embossed PE paper
<b>Surface:</b>	Matte white
<b>Adhesive:</b>	Polyacrylate
<b>Adhesive strength:</b>	Initial: 4.7 N/25 mm after 20 min: 4.3 N/25 mm after 24 hours: 9.0 N/25 mm
<b>Storage:</b>	1 year when storing properly at 15° - 20°C

### General Information

- Short-term floor graphic advertising without protective lamination for indoor application
- Easy and bubble-free application through air holes in the adhesive created by embossed liner
- Removable with reversible adhesive
- Can be used on smooth floor for coverings, e.g. on ceramic tiles
- Also suitable for vertical application
- Printable with latex, UV-curable, eco solvent and solvent inks
- Very good scratch resistance
- R9 certified

### Application

- Fairs and shop fitting
- Floor graphics and eye catchers

### Advantages

- Dry, bubble-free, clean, quick and easy application
- Reversible adhesive with very good adhesion
- Removable

## FloorGraphic 160 LUVESS M W air rem adh

## Technical Datasheet

L Latex · UV UV curing · ES Eco Solvent · S Solvent · M Matt · W White · air embossed cover  
rem removable · adh self-adhesive

Version: 03-2022

### Printing Properties

- Printable with latex, UV curing, eco solvent and solvent inks
- No bleedings even with high ink limit
- High color brilliance
- Fast drying

### Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The substrate must be dry, clean and smooth
- Roller or felt squeegee recommended to be without sharp edges
- To avoid fingerprints, the use of cotton gloves is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

### More information

- You can find more information on our products on [www.com2-c.de](http://www.com2-c.de)
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 15° - 20°C

### Available sizes

- 50 m x 137,0 cm (54'')

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.