


Inks**Application and Properties****Technical Data**

Thickness:	approx. 210µm
Composition:	100% polyester
Surface:	Satin white
Reverse side:	Glossy

General Information

- 100% polyester film
- Printable water-based pigment inks, with latex and UV curing inks
- High-quality satin inkjet coating enables extremely high ink limit
- Fast drying
- Extremely high color brilliance
- Good water and scratch resistance
- Dimension stability

Application

- Indoor advertising
- Specially developed for City lights and Light boxes
- For universal front print application

Advantages

- Water-resistant high-quality inkjet coating
- Fast drying, no bleeding even with high ink limits
- Strong and brilliant colors with extremely high ink application
- Dimension stability Polyester composite
- Material can be used without lamination

Printing Properties

- Excellent printability with water-based pigment, latex and UV-curable inks
- High ink limit application possible due to high-quality inkjet coating
- Very good and fast drying
- High color brilliance
- Waterproof inkjet coating

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 25°C

Available sizes

- 30 m x 106,7 cm (42") | 30 m x 137,2 cm (54") | 30 m x 152,4 cm (60")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.