

**Inks****Application and Properties****Technical Data**

<b>Thickness:</b>	approx. 160 µm
<b>Thickness with liner:</b>	approx. 295 µm
<b>Composition:</b>	100% polyester textile + adhesive + liner
<b>Surface:</b>	Matt white
<b>Adhesive:</b>	Unlimited repositionable acrylic adhesive
<b>Liner:</b>	Single sided siliconized

**General Information**

- Self-adhesive textile
- Silver backing, lightproof
- Easy to remove without leaving any residues (see processing instructions)
- Suitable for almost smooth, porous surfaces and textiles
- Printable with latex, UV curing, eco solvent and solvent inks
- High-quality matt inkjet coating enables high ink laydowns
- Fast drying
- High color brilliance
- Good water and scratch resistance

**Application**

- Suitable for Indoor advertising
- For customize wall/room design
- For the uses in Events and fair
- Quick and easy interior decoration

**Advantages**

- Splash resistant high-quality coating
- Dimensionally stable, no cracking
- Good adhesion onto almost every substrate
- Easily removable

### Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High ink limit application
- Fast drying
- High color brilliance

### Processing instructions

- The surface must be dry, clean and smooth.
- Not suitable for floor graphics, latex painted surfaces and structured - textured surfaces.
- Easy adhesion on smooth surfaces, painted wallpaper with a suitable paint (silicone and solvent free) - matte paint is recommended.
- The AllroundTex has a special reversible adhesive on the back, which allows easy adhesion and repositioning.
- We recommend to clearly check the surface suitability before any application.
- Before further processing, ensure that the prints are completely dry!
- Finished prints should be wrapped print side out for easy transport.
- Ideally, roll in a 6" Core (15cm) be suitable.
- Use roller or a felt squeegee and avoid sharp edges.
- To avoid fingerprints, the use of cotton gloves is recommended.
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

### More information

- You can find more information on our products on [www.com2-c.de](http://www.com2-c.de)
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 2 years when storing properly at 18° - 25°C

### Available sizes

- 30 m x 106,7 cm (42") | 30 m x 137,2 cm (54")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.