


Digitalvlies 150 LUV SM W adh FR

Technical Datasheet

L Latex · UV UV curing · SM Satin · W White · adh self-adhesive · FR Fire classification

Version: 03-2022

Inks



Application and Properties



Technical Data

Basic weight:	approx. 150 g/m ²
Composition:	100% fleece + adhesive + liner
Surface:	Satin white
Adhesive:	Water-based reversible adhesive with strong adhesion
Adhesive strength:	immediately: 2.0 – 2.7 N/cm After 10 m: 2.9 - 3.8 N/cm After 24 hours: 4.3 - 5.1 N/cm
Adhesive weight:	36 g/m ²
Liner:	Single sided siliconized paper
Liner basic weight:	135 g/m ²

General Information

- 100% non-woven wallpaper
- Printable with latex and UV curable inks
- Free from PVC, plasticizers, glass fibres and solvents
- No additional heavy metal compounds and formaldehyde
- Fast drying
- Photorealistic print quality
- Environmentally friendly
- Good water and scratch resistance
- Fire classification B1 according DIN 4102-1

Application

- Suitable for Indoor advertising
- For customize wall/room design
- For the uses in Events and fair
- Quick and easy interior decoration

Advantages

- Splash resistant high-quality coating
- Dimensionally stable, no cracking
- Good adhesion onto smooth and work-out wallpaper surfaces in combination with a suitable paint
- Easily removable

Digitalvlies 150 LUV SM W adh FR

Technical Datasheet

L Latex · UV UV curing · SM Satin · W White · adh self-adhesive · FR Fire classification

Version: 03-2022

Printing Properties

- Excellent printability with latex and UV-curable inks
- High ink limit application, no bleeding
- Fast drying
- High color brilliance

Processing instructions

- Ideal surface to work out this product must be dry, clean, dust-free, absorbent and smooth.
- The digital non-woven wallpaper has a special reversible adhesive for easy adhesion and repositioning.
- Not suitable for floor graphics application, latex painted and textured surfaces.
- Easy adhesion on smooth, wallpaper surfaces in combination with a suitable paint (solvent Free) we recommend a matt smooth paint
- Neatly final print cut, there is a good adhesion from edge to edge.
- If the strips of wallpaper are printed overlapping, cut off the white edges up to the motif, then align the strips on the wall in the area of the overlap. Make a double seam cut to ensure a clean seam.
- For a good adhesion work out, use a soft rubber roller or a soft dedicated brush to avoid bubbles.
- The printed material must be thoroughly dry and acclimatized before the adhesive.
- The optimal workings conditions during processing is 18° - 25°C, 40% - 65% RH

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 25°C

Available sizes

- 50 m x 124 cm (48, 8") | 50 m x 137,2 cm (54")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.

Digitalvlies 150 LUV SM W adh FR

Technical Datasheet

L Latex · UV UV curing · SM Satin · W White · adh self-adhesive · FR Fire classification

Version: 03-2022


- **Work out Instructions**



Untergrund ggf. reinigen.



Bahnbreiten ausloten und markieren.



Digitalvlies Stoß auf Stoß
verkleben.



Mehrmals repositionierbar, dazu mit beiden
Händen vorsichtig ablösen und wieder
aufkleben.