

Inks



Application and Properties



Technical Data

Thickness:	approx. 300µm
Basic Weight:	approx. 260g/m ²
Composition:	Polyester (100% PES)
Printing side:	Matt white
Reverse side:	Natural white

General Information

- Coated polyester fabric
- Printable with latex, UV curing, eco solvent and solvent inks
- High-quality matt inkjet coating enables high ink limits
- Fast drying
- High color brilliance
- Good water and scratch resistance

Application

- Fine -Art prints
- For Fine-Art and photo reproductions
- Suitable for frame stretching

Advantages

- Splash resistant high-quality coating
- Fast drying, no bleeding even with high ink limits
- Very good cracking resistant
- Very nice canvas looks like
- Dimensional Stability

Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High ink limit applicable due to high-quality inkjet coating
- Fast drying
- High color brilliance

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- This material is not washable
- For further processing, the room condition 18° - 25°C | 40% - 65% is very ideal.

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 25°C
- Possible that material width has 1-2mm difference.

Available sizes

- 30 m x 137 cm | 30 m x 152 cm | 50 m x 137 cm

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.