



**Inks****Application and Properties****Technical Data**

<b>Composition:</b>	monomeric plasticized PVC
<b>Thickness:</b>	approx. 100 µm
<b>Liner:</b>	Single side siliconized white paper
<b>Basic weight:</b>	135 g/m <sup>2</sup> siliconized paper
<b>Adhesive:</b>	Transparent, water-based dispersion dot formed adhesive
<b>Adhesive weight:</b>	approx. 15g/m <sup>2</sup>
<b>Surface:</b>	Matte, transparent

**General Information**

- Monomeric plasticized PVC
- Dot form transparent adhesive
- Printable with latex, UV-curable, eco solvent and solvent inks
- Matte and even surface
- Fast drying
- High color brilliance
- For short- and medium-term indoor application

**Application**

- For short so as medium-term indoor advertising application
- Easy application on both even and uneven surfaces
- Suitable for Events, trade fair and shop fittings
- Signs, marking

**Advantages**

- Easy drying, no bleeding even with high inks limit
- Good and reliable adhesion
- Easy and simple applications without bubbles or wrinkles
- Easy to remove without leaving any residue

**Printing properties**

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High color brilliance
- Fast drying
- Water and scratch resistant

**Processing instructions**

- Prints must be completely dry before further processing; a drying time of 24 hours is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%.

**More information**

- You can find more information on our product portfolio on [www.com2-c.de](http://www.com2-c.de)
- We can manufacture your product and customize the surface, lengths and widths individually to meet your requirements. We will need a MOQ.
- Always store rolls together with the label and batch number. Without the reference batch number, no complaints can be processed.
- Our tests are carried out in a standard climate condition.

**Available sizes**

- 50m x 106,7cm (42") | 50m x 137,0cm (54")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.