

Inks**Application and Properties****Technical Data**

Basic weight:	approx. 190 g/m ² (325 g/m ² liner)
Composition:	100% PES + adhesive + liner
Surface:	Matt white
Adhesive:	Semi-permanent acrylic adhesive, Solvent-based
Adhesive strength:	11 N/25 mm according to FTM1 - 24 h (average value)
Liner:	135 g/m ²

General Information

- Self-adhesive textile
- Easy to remove all residues from the substrates in a time lap of 6 months (see processing instructions)
- Printable with latex, UV curing, eco solvent and solvent inks
- High-quality matt inkjet coating enables high ink limits
- Fast drying
- High color brilliance
- Good water and scratch resistance

Application

- Suitable for Indoor advertising
- For customize wall/room design
- For the uses in Events and fair
- Quick and easy interior decoration

Advantages

- Splash resistant high-quality coating
- Dimensionally stable, no cracking
- Good adhesion onto almost every substrate
- Easily removable

Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High ink limit application
- Fast drying
- High color brilliance

Processing instructions

- The surface must be dry, clean and smooth.
- Not suitable for floor graphics, latex painted surfaces and structured - textured surfaces.
- Easy adhesion on smooth surfaces, painted wallpaper with a suitable paint (silicone and solvent free) - matte paint is recommended.
- The ImageTex has a special reversible adhesive on the back, which allows easy adhesion and repositioning.
- We recommend to clearly check the surface suitability before any application.
- Before further processing, ensure that the prints are completely dry!
- Finished prints should be wrapped print side out for easy transport.
- Ideally, roll in a 6" Core (15cm) be suitable.
- Use roller or a felt squeegee and avoid sharp edges.
- To avoid fingerprints, the use of cotton gloves is recommended.
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 2 years when storing properly at 18° - 25°C

Available sizes

- 30 m x 106,7 cm (42") | 30 m x 137,2 cm (54")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-commend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.