



Application and Properties



Technical Data

Film thickness:	Approx. 70 µm
Composition:	100% Polypropylen
Basic weight:	ca. 57 g/m ²
Surface:	Mat scratch-resistant surface
Adhesive:	Clear acrylic base, permanent
Adhesive strength (N/25mm):	20 Min. steel > 9 24h steel > 12
Liner:	135g/m ² paper

General Information

- 100% Polypropylen
- UV protection
- 5 years outdoor durability
- Environmentally friendly
- With permanent acrylate glue
- Without milky or silvering effect
- Scratch Resistant Surface
- Flame retardant according to European standard EN 13501-1:2019

Application

- Protective and finishing film for classic photos and digital prints, e.g PopUps
- Universal uses for indoors so as short to medium term outdoors applications
- Excellent quality lamination

Advantages

- PVC-free
- no silvering ghost effects after lamination
- With ultra-crystalline glue
- No shrinkage!
- Scratch Resistant Surface

Processing instructions

- When laminating on inkjet prints, it must be fully dried. A drying time of 24 hours is recommended. Due to the high density of polypropylene protective films, sufficient drying time (especially when using dark inks) is particularly important.
- It is also recommended not to cut the laminated material immediately after lamination. Leave it for another 24 hours so that the adhesive bonding suit better to the print medium
- The optimal room climate during processing is 18° - 25°C and a humidity of 40% - 65%.
- Do not expose to direct sunlight or heat sources.
- The product must be stored vertically so that its quality is not compromised.
- Shelf life: up to 5 years (with vertical exposure - normal Central European climate).
- Storage: 24 months from date of manufacture, applies only to material that has not yet been processed and stored under the following conditions: This material must be stored at a temperature of 20°C ± 5°C and 50% ± 5% relative humidity, without major climatic deviations.

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Shelf-life of this product is approx.12 months.
- Our tests are carried in standard climate conditions

Available sizes

- 50m x 137 cm (54'')

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.