

Inks



Application and Properties



Technical Data

Basic weight:	approx. 195 g/m ²
Composition:	100% polyester fabric from recycled plastic
Surface:	Semi-matt white, translucent
Stretch:	1-3%
Transmission:	40%
White Point (L*A*B*):	85.82* 3.58* -7.07*
Flame retardant:	B1, according to the DIN4102 norm.

General Information

- 100% polyester fabric from recycled plastic
- GRS-certificate (Global Recycled Standard)
- Printable with latex, UV curing, eco solvent and solvent inks
- Special InkJet coating enables the printing saturated colors and brilliant motifs for backlight application
- High flexibility
- No Crack
- Ideal for shipping even folded and ideal use in Alu-Frame framing systems
- REACH-compliant + free of harmful substances

Application

- Indoor lighting advertising
- Specially developed for backlit framing
- Blow-Up Ads

Advantages

- Rich, deep colors
- Almost no Cracking; can be sent folded
- Easy to stretch
- B1 Flame retardant t certified according to the DIN4102
- REACH-compliant + free of harmful substances

Printing Properties

- Excellent printability with latex, UV curing, eco solvent and solvent inks
- High ink limit application possible due to high-quality inkjet coating
- Very good and fast drying
- High color brilliance
- Waterproof inkjet coating

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging: 1 year when storing properly at 18° - 25°C

Available sizes

- 100 m x 260 cm (102") | 100 m x 320 cm (126")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-recommend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.