


BlackbackTex 250 DLUV M W FR

Technical Datasheet

D Dye Sub · L Latex · UV UV Curing · M Matt · W White · FR Flame Retardant

Version: 11-2024

Inks



Application and Properties



Technical Data

Basic weight:	approx. 260 g/m ²
Composition:	polyester fabric with a slight stretch content of 1-2%
Surface:	white, textile structure
Stretch:	1-2%
Back:	black, light-blocking layer
Opacity:	>95-100%
Flame retardant:	according to EN 13501

General Information

- Polyester fabric with a slight stretch content of 1-2%
- Printable with sublimation, latex and UV-curable inks
- Flexible blackout coating
- Very soft
- Impermeable to light
- High color brilliance
- Cold-cuttable without fraying

Application

- Indoor lighting application
- Textile advertising / tensioning
- Specially developed for backlit framing systems
- Ideal for UV-curing inks
- Trade fairs, POS

BlackbackTex 250 DLUV M W FR

Technical Datasheet

D Dye Sub · L Latex · UV UV Curing · M Matt · W White · FR Flame Retardant

Version: 11-2024

Printing Properties

- Excellent printability with latex and UV-curing inks
- High color brilliance

Processing instructions

- The print must be completely dry before further processing; a drying time of 24 hours is recommended
- Material is not washable.
- The optimal working condition during processing is 18° - 25°C and a relative humidity of 40% - 65%
- Calender settings: 195°C, 45 sec.

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 25°C

Available sizes

- 50 m x 320 cm | 50 m x 505 cm

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-command that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.