
Digitalvlies 180 LUV M W MegaTex Technical Datasheet


L Latex · UV UV curing · M Matte · W White · MegaTex adhesive· FR Fire classification

Version: 10-2026

Inks



Application and Properties



Technical Data

Basic weight:	approx. 180 g/m²
Composition:	100% fleece + special adhesive with line structure + backing paper
Surface:	Matte white
Adhesive:	Water-based reversible adhesive with strong adhesion
Adhesive strength:	**After 10 m**: 15,1 – 18,3 N/cm | **After 24 hours**: 20,2 – 21,6 N/cm
Adhesive weight:	24 g/m²
Liner:	Single sided siliconized paper
Liner basic weight:	120 g/m²

General Information

- 100% non-woven wallpaper
- Printable with latex and UV curable inks
- Free from PVC, plasticizers, glass fibres and solvents
- No additional heavy metal compounds and formaldehyde
- Fast drying
- Photorealistic print quality
- Environmentally friendly
- Good water and scratch resistance

Application

- Suitable for Indoor advertising
- For customize wall/room design
- For the uses in Events and fair
- Quick and easy interior decoration

Advantages

- Splash resistant high-quality coating
- Dimensionally stable, no cracking
- Good adhesion onto smooth and work-out wallpaper surfaces in combination with a suitable paint
- Easy to remove thanks to MegaTex line adhesive
- Can be removed without leaving any residue

com2C GmbH & Co. KG | Gänsekamp 37 | 32457 Porta Westfalica | Germany
Tel : + 49 57 33 87 85 88 | Fax : + 49 57 33 87 85 88 9 | Mail: info@com2-c.de | www.com2-c.de

Digitalvlies 180 LUV M W MegaTex Technical Datasheet

L Latex · UV UV curing · M Matte · W White · MegaTex adhesive· FR Fire classification

Version: 10-2026

Printing Properties

- Excellent printability with latex and UV-curable inks
- High ink limit application, no bleeding
- Fast drying
- High color brilliance

Processing instructions

- Ideal surface to work out this product must be dry, clean, dust-free, absorbent and smooth.
- The digital non-woven wallpaper has a special reversible adhesive for easy adhesion and repositioning.
- Not suitable for floor graphics application, latex painted and textured surfaces.
- Easy adhesion on smooth, wallpaper surfaces in combination with a suitable paint (solvent Free) we recommend a matt smooth paint, not suitable for high-energy, smooth surfaces
- Neatly final print cut, there is a good adhesion from edge to edge.
- If the strips of wallpaper are printed overlapping, cut off the white edges up to the motif, then align the strips on the wall in the area of the overlap. Make a double seam cut to ensure a clean seam.
- For a good adhesion work out, use a soft rubber roller or a soft dedicated brush to avoid bubbles.
- The printed material must be thoroughly dry and acclimatized before the adhesive.
- The optimal workings conditions during processing is 18° - 25°C, 40% - 65% RH

More information

- You can find more information on our products on www.com2-c.de
- The print side of the materials as well as the lengths and widths can be customized to your needs prior to a MOQ
- Always store rolls together with the label or batch number. No complaints can be processed without a batch number.
- Our tests are carried in standard climate conditions
- Shelf life in the original packaging, 1 year when storing properly at 18° - 25°C

Available sizes

- 50 m x 137,0 cm (54") | 50 m x 160,0 cm (63")

This technical information was made and assessed based on the latest technology and our experience. Due to various parameters and conditions under which the described product is used, we re-commend that every user should check the product for its suitability for the intended uses. A legally binding assurance of certain properties cannot be derived from our information. Errors and changes are subjected. With the release of a new version, this datasheet version will not be valid.

Digitalvlies 180 LUV M W MegaTex Technical Datasheet

L Latex · UV UV curing · M Matte · W White · MegaTex adhesive· FR Fire classification

Version: 10-2026